



# STOP FINISH

## Touch-up putty for small damage

C 2.1

### Product description

Fine one-pack putty for smoothing out small defects such as pores or voids in the substrate or isolated deeper sanding scratches.





### Technical characteristics

Shelf life: 24 months      Density: 1.780 g/cm<sup>3</sup>      Theoretical spreading rate: / m<sup>2</sup>/l at 1 µm  
Colour: grey      Solids content: 86.3% by weight

### Pre-treatment:

Clean with PK 700 or PK 900.  
Sand with P240.  
Clean with PK 1000.

Do not use STOP FINISH on bare metal.

	<b>Mixing ratio</b>	Stir well before use. STOP FINISH is ready for use. In rather high temperatures, the application performance can be improved by mixing STOP FINISH with 5% FR 500.
	<b>Potlife</b>	Seal product container tightly after each use.
	<b>Application</b>	Number of coats: 2 Film thickness: 40 µm
	<b>Drying</b>	Drying at 20°C: 2 hours Drying at 60°C: 20 min.
	<b>Sanding</b>	Wet with P400

Please refer to the EU Material Safety Data Sheet for product labelling as required by Directive 1999/45/EC and the respective national rules. The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.