



MULTI SPOT

Blending thinner

C 5

Product description






Blending thinner designed to melt in fade-out areas of UNO HD 420 and VOC-compliant R-M clears in blend-in repairs.

Technical characteristics

Shelf life:	36 months	Density:	0.881 g/cm ³	Theoretical spreading rate:	/ m ² /l at 1 μm
Colour:	transparent	Solids content:	3.6% by weight		

Pre-treatment

See process described in "UNO HD 420 Blending" B 2.

	Mixing ratio	The product is ready for use.		
	Spray viscosity	15 to 17 seconds ISO 4 cup at 20°C		
	Sprayguns	HVLP gravity-feed spraygun	1.3 – 1.5	0.7 bar at the nozzle
		Compliant gravity-feed spraygun	1.3 – 1.4	2.0 – 2.5 bar
	Application	Number of spraycoats:	2 – 3	
	Drying	Drying at 60°C:	30 min	
	Further treatment	See process described in "UNO HD 420 Blending" B 2.		

Please refer to the EU Material Safety Data Sheet for product labelling as required by Directive 1999/45/EC and the respective national rules. The products are suitable for professional use only.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.